

Karameh POE

No.	Item	Quantity	Specs
1	CPR Trolley	1	5 drawers with central Lock Extra foldable side shelf O2 cylinder holder trash bin
2	AMBU bags(adult size)	2	Maximum Tidal Volume: 1000 ml Pressure Limiting Valve: 560cm H2O- Maximum Ventilatory frequency: 40 Breath /Min Unfold dimension: 130 x310 Folded dimension: 130 x 120
3	AMBU bags(child size)	2	Including: silicon bag, PSF reservoir valve set, PSF intake valve set, Silicone mask 2-meter, Oxygen tubing, PVC reservoir bag, 60 cm H2O, Pop Off
4	AMBU bags(infant size)	2	Including: silicon bag, PSF reservoir valve set, PSF intake valve set, Silicone mask 2-meter, Oxygen tubing, PVC reservoir bag, 60 cm H2O Pop Off
5	Pulse Oximeter	4	Display type: OLED LCD SpO2 measurement range: 70% - 99% Accuracy: ±2% Resolution: ±1% PR measurement range: 30~240 BPM Accuracy: ±1 BPM or ±1% Power: 2 AAA 1.5 V alkaline battery Operation temperature: 5°C - 40°C Perfusion index: ≥0.2%, ±0.1% Power consumption: ≥30mAh Auto power off: 8 seconds
6	Portable blood pressure Monitor	3	With arrhythmia detection Particularly easy to use with one-button control panel Extra-large display, large buttons Fully automatic with fuzzy logic Integrated time and date 85 sets of memory Can be connected to mains adapter Washable cuff Transparent box for storage inclusive batteries
7	Multi parameter patient Monitor with movable stand	2	ECG: Lead mode 3 or 5 lead measurement and alarm range for HR 15-350BPM Scan speed :12.5mm/s, 25 mm/s , 50mm/s RESPIRATION: Method : R -F(RA-LL) Im penance measurement and alarm range 0-150 rpm apnea alarm 10-40s SPO2 Measurement and alarm range 0%-100% Accuracy: 70-100% +- 2% Measurement and alarm rang for PR 30-250 bpm NIBP: Method: Oscillometer Mode: manual /Auto/ continues Measurement interval continuous mode: 5 minutes measurement and alarm range 10-270mmHG Over pressure protection: dual protection for software and hardware Bp cuff: select adult , pediatric and neonatal cuff according to requirements TEMP Channel : dual-channel measurement and alarm range 0-50 C
8	Digital non touchable thermometer	4	Infrared sensor simplifies temperature measurement Dual mode - body and object Fahrenheit-Celsius switchable LED light to indicate the measuring position Measurement Accuracy (Laboratory)

9	AED Device	1	Display Format: LCD with Moving Bar, Device Advisory Messages, elapsed time, shock count and chest compression graph display A Complete Road Map for Resuscitation - Graphic User Interface- Built in Infra-Red Data Communication port. Rectilinear Biphasic Automated External Defibrillator with Visual and Voice Prompt Messages. - (Defibrillator & Analyzer & CPR Feedback). Operator Guide & operator Manual. Soft Carry Case. CPR D-Pads Adult for Defibrillation and Monitoring with CPR Feedback.
10	Surgical kit	10	Iris Scissor, Scalpel Handle, Operating Scissor, Artery Forceps, iodine bowel, tooth forceps, stitch remover, Needle holder
11	Delivery bed	1	Adjustable Head & Foot rests Compressed Sponge 5cm w/thick nylon cover Powder coated 4x4cm tubular frame, 1.8mm thickness Stainless steel bowl Horse shoe Patient Leg Holder
12	Delivery kit	10	Includes 8 Pieces with tray: Tenaculum forceps & Long scissor Uterine sound Speculum (S, M, L) Volvelle forceps & Sponge Forceps Artery forceps Iodine bowel
13	12 feet fridge	2	260 Liter, A+, Stainless Steel, Inverter
14	U/S device with gel	1	10 CRT display * Double activated probe connectors 100 frames permanent storage * Double USB ports General, Obstetrics, Gynecology measurement software package * Auto OB report Data Port: Video, S-Video, RS232, USB2.0, VGA
15	Auto scope	1	OTOSCOPE STANDARD
16	Ophthalmic scope	1	Ophthalmoscope head with lens wheel features 24 corrective lenses from -25 to +40 diopters zippered nylon storage case
17	Torch	2	INSTRULITE PEN LIGHT
18	Stairs for bed	2	Chrome Base Double foot step
19	Medical screen (curtain)	4	4 Folding Screen Powder coated frame Heavy duty Portable with wheels
20	Solution handles-IV stands	4	5 legs base Legs Heavy duty base Medical grade castors. Rotatable 4-hooks holder. Adjustable height
21	Glucose check	4	Test time: 5 seconds Sample type: Fresh capillary whole blood Calibration: Plasma-equivalent Assay method: Electrochemical Battery Life: 3000 tests Memory: 1000 test results
22	Suction device	1	Operating voltage: 230 V - 50 Hz Bottle capacity: 2 L Adjustable vacuum level: 0- -0.65 bar (0- -65 kPa) S Operating cycle: continuous
23	Autoclave device	1	Stainless-steel chamber. Large graphic display BMS STERIL MAXIMUM is a class B autoclave with 10 different sterilization cycles and 2 test cycles ("Vacuum Test" and "Helix/ Bowie & Dick Test"). Capacity: 18 Liter
24	Medical bed	2	Two sections Movable back Mattress & pillows included Standard Dimension & Heavy duty
25	Wheel chair	2	Slandered steel wheel chair

26	Standing exam light	2	white LEDs Strength of 50,000 lux Adjustable focus handle
27	O2 cylinder	2	10 liter with regulator and face mask and nose nozzle

Jaber POE

No.	Item	quantity
1	CPR Trolley	1
2	AMBU bags(adult size)	2
3	AMBU bags(child size)	2
4	AMBU bags(infant size)	2
5	pulse Oximeter	4
6	portable blood pressure Monitor	3
7	Multi parameter patient Monitor with movable stand	2
8	Digital non touchable thermometer	4
9	AED Device	1
10	Surgical kit	10
11	delivery bed	1
12	Delivery kit	10
13	12 feet fridge	2
14	U/S device with gel	1
15	Auto scope	1
16	ophthalmic scope	1
17	torch	2
18	stairs for bed	2
19	medical screen	4
20	solution handles	4
21	glucose check	4
22	suction device	1
23	autoclave device	1
24	Medical bed	2
25	wheel chair	2
26	Standing exam light	2
27	O2 cylinder with regulator and face mask and nose nozzle	2